

CALIBER 80 SUB

UNDERWATER / SUBACQUEI

TECHNICAL DATA / DATI TECNICI



IP68 (5 meter underwater /
5 metri in immersione)



6W / 9W / 9W RGBW



> 90



2200K / 2450K / 2700K / 3000K / 4000K /
RGBW (W=3000) / DW (1800÷3000K)



10° / 30° / 50° / 10°x45° / Satin *Satinato* /
30° RGBW / 20° DW / 50° DW




FINISHES / FINITURE



.12

Electropolished
stainless steel AISI316L


TECHNICAL DRAWING / DISEGNO TECNICO



measure unit / unità di misura: mm

PRODUCT CODE / CODICE PRODOTTO

C8S = CALIBER 80 SUB



Select one component from each column to specify a complete configuration:
 Seleziona un componente per ogni colonna per la configurazione completa:

LED colour / Colore LED	Optics / Ottiche	Finish / Finiture	Power / Potenza
22 = 2200K * 25 = 2450K * 27 = 2700K 30 = 3000K 40 = 4000K FC = RGBW DW = Dim to Warm	N = 10° M = 30° (20° DW) (30° RGBW) W = 50° (50° DW) E = 10° x 45° S = Satin / <i>Satinato</i> (* no for 2200K/2450K)	12 = Electropolished stainless steel AISI316L / Acciaio INOX elettrolucidato AISI316L	06 = 6W 09 = 9W CC = 4x700mA RGBW

Standard configuration example:
 Esempio di configurazione standard:

C8S.30.N.12.09 | Caliber 80 sub 3000K 10° optics electropolished stainless steel / acciaio INOX elettrolucidato 9W

