

# CALIBER 80

INGROUND / INCASSI A TERRA

## TECHNICAL DATA / DATI TECNICI



IP68 (not for permanent immersion /  
non per immersione permanente)



6W / 9W / 9W RGBW /  
12W DW



> 90



2200K / 2450K / 2700K / 3000K / 4000K /  
RGBW (W=3000) / DW (1800÷3000K)



10° / 30° / 50° / 10°x45° / Satin *Satinato* /  
35° RGBW / 20° DW / 50° DW




## FINISHES / FINITURE



**.03**

Stainless steel  
AISI316L



**.10**


Aged solid brass



**.21**

Pre-aged solid brass


## TECHNICAL DRAWING / DISEGNO TECNICO



measure unit / unità di misura: mm

## PRODUCT CODE / CODICE PRODOTTO

### C80 = CALIBER 80



Select one component from each column to specify a complete configuration:  
 Seleziona un componente per ogni colonna per la configurazione completa:

| LED colour /<br>Colore LED                                                                              | Optics / Ottiche                                                                                                                 | Finish / Finiture                                                                                                                                               | Power / Potenza                                          |
|---------------------------------------------------------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------------------|-----------------------------------------------------------------------------------------------------------------------------------------------------------------|----------------------------------------------------------|
| 22 = 2200K *<br>25 = 2450K *<br>27 = 2700K<br>30 = 3000K<br>40 = 4000K<br>FC = RGBW<br>DW = Dim to Warm | N = 10°<br>M = 30° (20° DW)<br>(35° RGBW)<br>W = 50° (50° DW)<br>E = 10° x 45°<br>S = Satin / Satinato<br>(* no for 2200K/2450K) | 03 = Stainless steel<br>AISI316L / Acciaio<br>INOX AISI316L<br>10 = Aged solid brass /<br>Ottone anticato<br>21 = Pre-aged solid brass /<br>Ottone pre-anticato | 06 = 6W<br>09 = 9W<br>CC = 4x700mA RGBW<br>350mA-14mA DW |

Standard configuration example:  
 Esempio di configurazione standard:

**C80.30.N.03.09** | Caliber 80 3000K 10°optics stainless steel / acciaio INOX 9W



Project: Private house, London